



JA-163A RB Wireless outdoor battery powered siren

The JA-163A RB siren is a component of the JABLOTRON 100+ system. It is used to indicate alarms outdoors and for supplementary acoustic indication. The siren is powered by a lithium battery, completely without the need of any external power supply.

○ [Declaration of conformity - JA-163A RB \(PDF 315.48 kB\)](#)



Description

The siren consists of a JA-163A-BASE-RB base with the electronic components, a BAT-100A lithium battery and a top enclosure of the JA-1X1A-C-xx series. The enclosures are supplied in several colour designs. It occupies one position in the system.

The components of the JA-163A RB product (base, top enclosure and battery) are supplied separately. The reason is free selection from a number of top enclosures and the transport conditions of the battery.



JA-163A-BASE-RB - bottom part with electronics



JA-1X1A-C-ST - stainless steel cover



JA-1X1A-C-ST-B - stainless steel cover



JA-1X1A-C-WH - plastic cover - white



JA-1X1A-C-WH-B - plastic cover - white



JA-1X1A-C-GR - plastic cover - gray



JA-1X1A-C-GR-B - plastic cover - gray

Technical specifications

Power	Lithium battery 3.6 V/13 Ah type BAT-100A, BAT-100A.01 (up to 2 batteries can be used) Please note: battery is not included
Current consumption (nominal/maximal)	0.3/1000 mA
Battery low voltage	≤ 2.8 V
Typical battery lifetime	approx. 5 years (for basic settings)
Communication frequency	868.1 MHz, JABLOTRON protocol
Communication range	approx. 300 m (open area)
Antenna internal, external	can be used, type AN-868
Activation lost integrity	acoustic tamper alarm (110 min)
Piezo electric siren	100 dB/m
Dimensions (cover included)	200 x 300 x 70 mm
Weight	434 g
Classification	security grade 2/environmental class IV
- according to	EN 50131-1, EN 50131-4, EN 50131-5-3
- environment	general outdoor

- operational temperature range	-20 to +60°C
- power supply	type W
- operational humidity	75% (95% 30 days) RH, non-condensing
- certification body	Trezor Test s.r.o. (no. 3025)
Security grade	IP44
Also complies with	ETSI EN 300 220, EN 50130-4, EN 55022, EN 60950-1
Can be operated to	ERC REC 70-03