


The JA-112P / JA-112P (G) BUS PIR motion detector

Technical specifications

Power	from the control panel BUS 12 V (9 ... 15 V)
Current consumption in standby mode	5 mA
Current consumption for cable choice (maximum)	16 mA
Recommended installation height	2.5 m above the floor
Detection angle/detection range	90°/12 m
Dimensions	62 x 110 x 40 mm
Weight	77 g
Classification	Grade 2/Environmental class II (According to EN 50131-1)
Operational environment	Indoor general
Operational temperature range	-10 °C to +40 °C
Average operational humidity	75 % RH, non-condensing
Certification body	Trezor Test s.r.o. (no. 3025), KIWA
Complies with	EN 50131-1, EN 50131-2-2 EN 50130-4, EN 55032, EN 50581

T 031 (comply by installation in the center of the inner corner)

Recommended screw 2 x  ø 3.5 x 40 mm (countersunk head)



JABLOTRON ALARMS a.s. hereby declares that the JA-112P is in compliance with the relevant European Union harmonisation legislation: Directives No: 2014/35/EU, 2014/30/EU, 2011/65/EU, when used as intended. The original of the conformity assessment can be found at www.jablotron.com – the Downloads section

Note: Disposing of this product correctly will help save valuable resources and prevent any potential negative effects on human health and the environment, which could otherwise arise from inappropriate waste handling. Please return the product to the dealer or contact your local authority for further details of your nearest designated collection point.



The complete version of the manual can be found at:
https://bit.ly/JABLOTRON_JA-112P

JABLOTRON ALARMS a.s.
Pod Skalkou 4567/33 | 46601 Jablonec n. N.
Czech Republic | www.JABLOTRON.com

UK
CA

JABLOTRON