


## JA-110P Bus PIR motion detector

### Technical specifications

Power .....	from the control panel bus 12 V DC (9 ... 15 V)
Current consumption in standby mode .....	5 mA
Current consumption for cable choice (maximal).....	10 mA
Recommended installation height .....	2.5 m above the floor
Detection angle / detection coverage .....	110 degrees/12 m (with standard lens)
Dimensions .....	60 x 95 x 55 mm
Weight .....	75 g
Classification .....	Security grade 2/Environmental class II (EN 50131-1)
Operational environment.....	Indoor general
Operating temperature range.....	-10 °C to +40 °C
Average operating humidity .....	75 % RH, without condensation
Certification body .....	Trezor Test s.r.o. (no. 3025), Telefication B.V.
Complies with .....	EN50131-1, EN50131-2-2, EN50130-4, EN55032, EN 50581, T 031
Recommended screw .....	2x  ø 3.5 x 40 mm (countersunk head)



JABLOTRON ALARMS a.s. hereby declares that the JA-110P product is in a compliance with the relevant Union harmonisation legislation: Directives No: 2014/30/EU, 2011/65/EU if it is used as intended. The original of the conformity assessment can be found at [www.jablotron.com](http://www.jablotron.com) - Section Downloads.

**Note:** Although this product does not contain any harmful materials we suggest you return the product to the dealer or directly to the producer after use. For more detailed information visit [www.jablotron.com](http://www.jablotron.com).



The complete version of the manual can be found at:  
[https://bit.ly/JABLOTRON\\_JA-110P](https://bit.ly/JABLOTRON_JA-110P)

JABLOTRON ALARMS a.s.  
Pod Skalkou 4567/3 | 46601 Jablonec n. N.  
Czech Republic | [www.JABLOTRON.com](http://www.JABLOTRON.com)

**JABLOTRON**