


## The JA-110P PET Bus PIR motion detector with basic pet immunity

### Technical specifications

Power .....	from the control panel BUS 12 V (9 ... 15 V)
Current consumption in standby mode .....	5 mA
Current consumption for cable choice (maximum) .....	10 mA
Recommended installation height.....	2 m above the floor
Detection angle/detection coverage .....	90°/12 m
Detection angle/detection coverage – pet immunity .....	90°/7 m
Dimensions .....	60 x 95 x 55 mm
Weight .....	75 g
Classification.....	Grade 2/II. indoor general (According to EN 50131-1)
Operational environment.....	Indoor general
Operational temperature range .....	-10 °C to +40 °C
Average operational humidity.....	75 % RH, non-condensing
Certification body.....	Trezor Test s.r.o. (no. 3025)
Also complies with.....	EN 50131-1 ed. 2+A1+A2, EN 50131-2-2 EN 50130-4 ed. 2+A1, EN 55032, EN 50581
Recommended screw .....	2x  ø 3.5 x 40 mm (countersunk head)



JABLOTRON ALARMS a.s. hereby declares that the JA-110P PET is in compliance with the relevant European Union harmonisation legislation: Directives No: 2014/35/EU, 2014/30/EU, 2011/65/EU, when used as intended. The original of the conformity assessment can be found at [www.jablotron.com](http://www.jablotron.com) – the Downloads section

**Note:** Although this product does not contain any harmful materials we suggest you return the product to the dealer or directly to the producer after use.



The complete version of the manual can be found at:  
[https://bit.ly/JABLOTRON\\_JA-110P-PET](https://bit.ly/JABLOTRON_JA-110P-PET)

JABLOTRON ALARMS a.s.  
Pod Skalkou 4567/33 | 46601 Jablonec n. N.  
Czech Republic | [www.JABLOTRON.com](http://www.JABLOTRON.com) **JABLOTRON**